



Stiff Stay Exclusion Fencing Fencing / Stiff Stay

- Stiff Stay knot to increase rigidity of fence
- Built to withstand impact
- Heavily galvanised
- Made in Australia



Highly engineered, tight cross-over Stiff Stay® knot



Stiff Stay® prefabricated fencing features a tight cross-overStiff Stay prefabricated fencing features a tight cross-overknot manufactured on the Stiff Stay machine. The name Stiff Stay is trademarked to Whites and is made in Australia to the highest standards, exclusively from Whites Albury Manufacturing plant in regional Australia, using premium grade wire.

Specifically designed to protect by providing a barrier against smaller marsupials, dogs, pigs and feral animals, Stiff Stay® Exclusion Fencing is produced with graduated line wire spacings. The tighter 15cm stay spacings further improve its ability to withstand impact.



Features high tensile 2.8mm line wires at top and bottom; 2.5mm high tensile line wires with graduated spacings; 2.5mm vertical stay wires.

Product Data Sheet

Code	Product	Tensile Strength	Roll Length	Roll Weight	Pallet Qty.	Galv. Coating	Top/Base Wire
10235	8/80/15	High	100m	62kg	9	Heavy Galv.	2.8mm
10238	8/90/15	High	100m	63kg	9	Heavy Galv.	2.8mm
10239	8/115/15	High	100m	69kg	9	Heavy Galv.	2.8mm
10285	11/90/15 w/ 30cm footer	High	100m	96kg	9	Heavy Galv.	2.8mm
10289	11/90/15	High	100m	75kg	9	Heavy Galv.	2.8mm
10255	13/90/15 w/ 30cm footer	High	100m	106kg	9	Heavy Galv.	2.8mm
10251	13/90/15	High	100m	86kg	9	Heavy Galv.	2.8mm
10259	13/115/15	High	100m	92kg	9	Heavy Galv.	2.8mm
10260	15/150/15	High	100m	118kg	9	Heavy Galv.	2.8mm

Not all products available in all areas of Australia